



**PRESERVER 2 HALF DOORS -20°C**  
**20 LEVELS 400x600 - INLET 400**  
**COMPACT TYPE - REINFORCED COLD**

No contractual pictures

**CAPACITIES**

2 doors for preserver -20°C, i.e. 20 trays 400x600

1 tray 400x600 per level  
 tray inlet 400m



**DESCRIPTION**

- Isothermal panels made of polyurethan foam, 90 mm thick, density 35 kgm<sup>3</sup>, high insulation coefficient Lambda = 0,022
- Outside is pre-enameled
- Interior and front are made of STAINLESS STEEL
- Door hinges on the right hand side
- Stainless steel slipper-guides at 63mm pitch
- Machine on screw-jacks 150mm high.
- Régulation : electronical thermostat
- Remote compressor
- Delivered dismantled

**OPTIONS**

- Extension module of 2 doors in positive cold
- Outside made of stainless steel

Width	Depth	Height	Opened door depth	Door passage	Net Weight	Electrical Supply	Absorbed power	Absorbed current
860 mm	980 mm	2175 mm	1524 mm	400 mm	179 kg	230V MONO 50Hz	1.1 KW	4.7 A
			Cold power -30/+32°C		Defrosting power	Cooling fluid	Cooling fluid load	
			1 CV	860 W	460 W	R404A	1.9 kg	

Indicated height of the machine is determined for remote compressors

- provide +100mm for gas solenoid valves, tubes and cables
- provide +350mm in case of compressors located on the roof