



PRESERVER 4 HALF DOORS -20°C
39 LEVELS 600x800 - INLET 600
REINFORCED COLD

No contractual pictures

CAPACITIES

4 doors for preserver -20°C i.e. 78 trays 400x600

2 trays 400x600 or 1 tray 600x800 per level
 Tray inlet: 600 mm



DESCRIPTION

- Isothermal panels made of polyurethan foam, 90 mm thick, density 35 kgm³, high insulation coefficient Lambda = 0,022
- Outside is pre-enameled
- Interior and front are made of STAINLESS STEEL
- Door hinges on the right hand side for the 2 right doors and left hand side for the other doors
- Stainless steel slipper-guides at 63mm pitch
- Machine on screw-jacks 150mm high.
- Régulation : electronical thermostat
- Remote compressor
- Delivered dismantled

OPTIONS

- Extension module of 2 doors in positive cold
- Outside made of stainless steel
- Supply of 48 trays 400x600 and 6 basquets

Width	Depth	Height	Opened door depth	Door passage	Net Weight	Electrical Supply	Absorbed power	Absorbed current
1904 mm	1215 mm	2255 mm	1965 mm	600 mm	380 kg	400V TRI 50Hz	2.8 KW	4.8 A
			Cold power -30/+32°C		Defrosting power	Cooling fluid	Cooling fluid load	
			3 CV	2105 W	1550 W	R404A	2.2 kg	

Indicated height of the machine is determined for remote compressors

- provide +100mm for gas solenoid valves, tubes and cables
- provide +350mm in case of compressors located on the roof