



DEEP FREEZER / PRESERVER - 6 HALF DOORS 400x600
15 LEVELS AT -35°C / 64 LEVELS AT -20°C - INLET 400
2 COMPRESSORS - COMPACT TYPE - REINFORCED COLD

No contractual pictures



CAPACITIES

2 doors for deep freezer -35°C, i.e. 15 trays 400x600
 6 doors for preserver -20°C, i.e. 64 trays 400x600

1 tray 400x600 per level
 tray inlet 400mm

Deep freezing capacity for fresh dough +20°C to -18°C: 15 kg/hour



DESCRIPTION

- Isothermal panels made of polyurethan foam, 90 mm thick, density 35 kgm³, high insulation coefficient Lambda = 0,022
- Outside is pre-enameled
- Interior and front are made of STAINLESS STEEL
- Door hinges on the right hand side for end right doors
- Door hinges on the left hand side for the other doors
- Stainless steel slipper-guides: 63 mm pitch (adjustable every 21mm), except in deep freezer top compartment = 4 levels at 69mm pitch
- Machine on screw-jacks 150mm high.
- Régulation : electronical thermostats - mechanical timer
- Remote compressors
- Delivered dismantled

OPTIONS

- Extension module of 2 doors in positive cold

Regulation:

- Electronic control board RXP4D

Width	Depth	Height	Opened door depth	Door passage	Net Weight	Electrical Supply	Absorbed power	Absorbed current
2850 mm	980 mm	2175 mm	1524 mm	400 mm	752 kg	400V TRI 50Hz	4.2 KW	9.2 A

Cold power -30/+32°C				Defrosting power		Cooling fluid	Cooling fluid load
Deep Freezer		Freezer		Deep Freezer	Freezer		
2 CV	1628 W	2 CV	1628 W	1000 W	1000 W	R404A	2.2/2.2 kg

Indicated height of the machine is determined for remote compressors

- provide +100mm for gas solenoid valves, tubes and cables
- provide +350mm in case of compressors located on the roof