



DEEP FREEZER 2 HALF DOORS -35°C
15 LEVELS 400x600 - INLET 400
COMPACT TYPE - REINFORCED COLD

No contractual pictures



CAPACITIES

2 doors for deep freezer -35°C, i.e. 15 trays 400x600

1 tray 400x600 per level
 tray inlet 400mm

Deep freezing capacity for fresh dough +20°C to -18°C: 15 kg/hour



DESCRIPTION

- Isothermal panels made of polyurethan foam, 90 mm thick, density 35 kgm³, high insulation coefficient Lambda = 0,022
- Outside is pre-enameled
- Interior and front are made of STAINLESS STEEL
- Door hinges on the right hand
- Stainless steel slipper-guides, 4 levels at 69mm pitch, 11 levels at 63mm pitch
- Machine on screw-jacks 150mm high.
- Régulation : electronical thermostat - Mechanical timer
- Remote compressor
- Delivered dismantled

OPTIONS

- Extension module of 2 doors in positive cold

Regulation:

- Electronic control board RXP4S

Width	Depth	Height	Opened door depth	Door passage	Net Weight	Electrical Supply	Absorbed power	Absorbed current
850 mm	980 mm	2175 mm	1524 mm	400 mm	250 kg	400V TRI 50Hz	2.1 KW	5 A
			Cold power -30/+32°C		Defrosting power	Cooling fluid	Cooling fluid load	
			2 CV	1628 W	1000 W	R404A	2.2 kg	

Indicated height of the machine is determined for remote compressors

- provide +100mm for gas solenoid valves, tubes and cables
- provide +350mm in case of compressors located on the roof